

Bronze Low Pressure Gas Valves - Plug Style

Brass body and plug manually operated low pressure natural or propane gas valve for use indoors on house piping systems between the meter outlet and the inlet connection of the gas appliance at ambient temperatures of 32 to 125 degrees Fahrenheit.



10598 Lever Handle with Check

2 PSIG

Inlet: FIP Thread
Outlet: FIP Thread

Sizes: 1/4", 3/8", 1/2", 3/4", 1",


1 1/4", 1 1/2", 2"




NOTE: 1/2" and 3/4" valves are pressure rated at 5 PSIG.

SIZE	Α	В	С	D	E
1/2	1	1	1.875	1.391	1.266
3/4	1.156	1.156	2.188	1.531	1.391

SIZE	Α	В	С	D	E
1/4	.844	.844	1.625	1.078	.984
3/8	.813	.813	1.625	1.078	.984
1	1.375	1.375	2.75	1.813	1.563
1 1/4	1.609	1.609	3.125	2.125	1.938
1 1/2	1.688	1.688	3.5	2.406	2.094
2	2.188	2.188	3.875	2.875	2.375





All other sizes top check

NOTE: Valves are designed for use with natural, manufactured or LP gas only.

All A.Y. McDonald plug style gas valves are factory set. DO NOT TAMPER WITH BOTTOM NUT.