



100

Screwed Ends
Metal Disc
Body Material: Bronze Conforming to ASTM B62
Sizes 3/8" to 1-1/4"
Replaceable Insert (Part No. 100A)



50, 50T
 50LS, 50TLS
 53
 350T, 350TLS

SPRING LOADED LIFT CHECK VALVES

Complies with MSS-SP-80-97
 200 lbs. WSP @ 406°F Max, (300 lbs. WSP - 350T, 350TLS)
 400 lbs. WOG, (600 lbs. WOG - 350T, 350TLS)
 100% Pressure Tested
Screwed Ends
Union Cap Design
Body Material: Bronze
Sizes 1/4" to 2" (1/2" to 2" - 350T, 350TLS)
 "50, 50T" designed for non-return control of water, oil or gas.
 "50LS, 50TLS" are similar to "50" model except that there is no spring pressure above the disc.
 "53" has a solid piece of Teflon replacing the disc and holder assembly.
 "350T, 350TLS" are heavy duty 300 lb. class for high pressure.



67

GROOVED CHECK VALVES

Size 4"
 250 lbs. WOG (Specify Service if other than cold water)
 100% Hydrostatic Tested
Ductile Iron Body
"O" Ring Seals
Bronze Clapper and Seat Ring
Stainless Steel Spring Closing
UL Listed/FM Approved
 Install for use in grooved end piping systems. Compact and easy to handle. SS torsion spring provides tight closure.

THREADED CHECK VALVES

Size 4"
 250 lbs. WOG (Specify Service if other than cold water)